

ACETAL TWO-PIECE CLAMPING COLLARS **N2C-SERIES**



- Ideal for wash down environments, will not rust or corrode
- USDA approved
- Easily installed where major disassembly would otherwise be required



For 3D
Models &
2D Sales
Drawings

DIMENSION
BORE, INCH

TOLERANCE
+0.003 / -0.000

PART NUMBER	PRODUCT SPECIFICATIONS					
	ACETAL	BORE	OD	WIDTH	SCREW SIZE	APPROX WEIGHT (OZ)
N2C-025		1/4	5/8	5/16	4-40 x 3/8	0.22
N2C-037		3/8	7/8	11/32	6-32 x 3/8	0.38
N2C-050		1/2	1 1/8	13/32	8-32 x 1/2	0.62
N2C-062		5/8	1 5/16	7/16	10-32 x 1/2	0.88
N2C-075		3/4	1 1/2	1/2	1/4-28 x 5/8	1.30
N2C-100		1	1 3/4	1/2	1/4-28 x 5/8	1.85

Acetal collars include stainless steel screws

TWO-PIECE CLAMPING COLLARS DOUBLE WIDE **D2C-SERIES**



- Ideal for space constrained applications
- High axial load capacity
- Easily installed where major disassembly would otherwise be required
- Design fully engages the shaft without marring
- Effective on both hard and soft shafts



For 3D
Models &
2D Sales
Drawings

DIMENSION
BORE, INCH

TOLERANCE
+0.003 / -0.000

PART NUMBER			PRODUCT SPECIFICATIONS				
BLACK OXIDE STEEL	STAINLESS STEEL	ALUMINUM	BORE	OD	WIDTH	SCREW SIZE	APPROX WEIGHT (OZ)
D2C-012	D2C-012-S	D2C-012-A	1/8	11/16	5/8	4-40 x 3/8	0.87
D2C-018	D2C-018-S	D2C-018-A	3/16	11/16	5/8	4-40 x 3/8	0.79
D2C-025	D2C-025-S	D2C-025-A	1/4	11/16	5/8	4-40 x 3/8	0.77
D2C-031	D2C-031-S	D2C-031-A	5/16	11/16	5/8	4-40 x 3/8	0.69
D2C-037	D2C-037-S	D2C-037-A	3/8	7/8	3/4	6-32 x 3/8	1.44
D2C-050	D2C-050-S	D2C-050-A	1/2	1 1/8	7/8	8-32 x 1/2	2.54
D2C-062	D2C-062-S	D2C-062-A	5/8	1 5/16	15/16	10-32 x 1/2	3.64
D2C-075	D2C-075-S	D2C-075-A	3/4	1 1/2	1 1/16	1/4-28 x 5/8	5.24
D2C-087	D2C-087-S	D2C-087-A	7/8	1 5/8	1 1/16	1/4-28 x 5/8	5.69
D2C-100	D2C-100-S	D2C-100-A	1	1 3/4	1 1/16	1/4-28 x 5/8	6.24

TWO-PIECE CLAMPING COLLARS WITH KEYWAY **2C-KW-SERIES**



- For use on keyed shafts
- Easily installed where major disassembly would otherwise be required
- Design fully engages the shaft without marring
- Greater axial holding power than set screw or one-piece collars
- Effective on both hard and soft shafts



For 3D
Models &
2D Sales
Drawings

DIMENSION
BORE, INCH

TOLERANCE
+0.003 / -0.000

PART NUMBER			PRODUCT SPECIFICATIONS					
BLACK OXIDE STEEL	STAINLESS STEEL	ALUMINUM	BORE	OD	WIDTH	SCREW SIZE	KEYWAY SIZE	APPROX WEIGHT (OZ)
2C-037-KW	2C-037-S-KW	2C-037-A-KW	3/8	7/8	3/8	6-32 x 3/8	3/32	0.71
2C-050-KW	2C-050-S-KW	2C-050-A-KW	1/2	1 1/8	13/32	8-32 x 1/2	1/8	1.26
2C-062-KW	2C-062-S-KW	2C-062-A-KW	5/8	1 5/16	7/16	10-32 x 1/2	3/16	1.80
2C-075-KW	2C-075-S-KW	2C-075-A-KW	3/4	1 1/2	1/2	1/4-28 x 5/8	3/16	2.60
2C-100-KW	2C-100-S-KW	2C-100-A-KW	1	1 3/4	1/2	1/4-28 x 5/8	1/4	3.10
2C-125-KW	2C-125-S-KW	2C-125-A-KW	1 1/4	2 1/16	1/2	1/4-28 x 3/4	1/4	4.22
2C-150-KW	2C-150-S-KW	2C-150-A-KW	1 1/2	2 3/8	9/16	1/4-28 x 3/4	3/8	6.04
2C-200-KW	2C-200-S-KW	2C-200-A-KW	2	3	11/16	5/16-24 x 1	1/2	10.97
2C-218-KW	2C-218-S-KW	2C-218-A-KW	2 3/16	3 1/4	3/4	5/16-24 x 1	1/2	13.96