

LIGHTWEIGHT SET SCREW COLLARS **LC-SERIES**

- Smaller width ideal for limited spaces
- Traditional cost effective collar
- Effective on both hard and soft shafts

PART NUMBER	PRODUCT SPECIFICATIONS				
ZINC PLATED STEEL	BORE	OD	WIDTH	SCREW SIZE	APPROX WEIGHT (OZ)
LC-025	1/4	1/2	1/4	8-32 x 1/8	0.15
LC-031	5/16	9/16	1/4	8-32 x 1/8	0.18
LC-037	3/8	5/8	5/16	10-32 x 1/8	0.25
LC-043	7/16	5/8	3/8	10-32 x 1/8	0.24
LC-050	1/2	7/8	3/8	1/4-20 x 3/16	0.65
LC-062	5/8	1	7/16	1/4-20 x 3/16	0.90
LC-075	3/4	1 1/8	7/16	1/4-20 x 3/16	1.01
LC-087	7/8	1 1/4	7/16	1/4-20 x 3/16	1.16
LC-100	1	1 1/2	7/16	1/4-20 x 1/4	1.83
LC-125	1 1/4	1 3/4	1/2	5/16-18 x 1/4	2.50

Zinc plated collars have black oxide coated screws



DIMENSION	
BORE, INCH	
BORE SIZE	BORE TOLERANCE
1/4" TO 1/2"	+0.0005 / +0.0025
5/8" TO 1 1/4"	+0.0005 / +0.0030

For 3D Models & 2D Sales Drawings



TWO-HOLE SET SCREW COLLARS **C-2H-SERIES**

- Load capacity is nearly doubled by adding a second screw
- Set screws are at 90°
- Effective on both hard and soft shafts

PART NUMBER	PRODUCT SPECIFICATIONS				
BLACK OXIDE STEEL	BORE	OD	WIDTH	SCREW SIZE	APPROX WEIGHT (OZ)
C-025-2H @ 90°	1/4	1/2	5/16	10-32 x 1/8	0.20
C-037-2H @ 90°	3/8	3/4	3/8	1/4-20 x 3/16	0.50
C-050-2H @ 90°	1/2	1	7/16	1/4-20 x 1/4	1.10
C-062-2H @ 90°	5/8	1 1/8	1/2	5/16-18 x 1/4	1.50
C-075-2H @ 90°	3/4	1 1/4	9/16	5/16-18 x 1/4	1.90
C-100-2H @ 90°	1	1 1/2	5/8	5/16-24 x 1/4	2.78
C-125-2H @ 90°	1 1/4	2	11/16	3/8-16 x 3/8	5.70
C-150-2H @ 90°	1 1/2	2 1/4	3/4	3/8-16 x 3/8	7.20
C-200-2H @ 90°	2	3	7/8	1/2-13 x 1/2	14.90



DIMENSION	
BORE, INCH	
TOLERANCE	
+0.003 / -0.000	

For 3D Models & 2D Sales Drawings



SET SCREW COLLARS WITH KEYWAY **C-KW-SERIES**

- For use on keyed shafts
- Traditional cost effective collar
- Effective on both hard and soft shafts

PART NUMBER			PRODUCT SPECIFICATIONS					
BLACK OXIDE STEEL	STAINLESS STEEL	ALUMINUM	BORE	OD	WIDTH	SCREW SIZE	KEYWAY SIZE	APPROX WEIGHT (OZ)
C-100-KW	C-100-S-KW	C-100-A-KW	1	1 1/2	5/8	5/16-24 x 1/4	1/4	2.78
C-125-KW	C-125-S-KW	C-125-A-KW	1 1/4	2	11/16	3/8-16 x 1/4	1/4	5.70
C-150-KW	C-150-S-KW	C-150-A-KW	1 1/2	2 1/4	3/4	3/8-16 x 1/4	3/8	7.20
C-200-KW	C-200-S-KW	C-200-A-KW	2	3	7/8	1/2-13 x 3/8	1/2	14.90

Keyway on bore size 1" is 90° to the screw



DIMENSION	
BORE, INCH	
TOLERANCE	
+0.003 / -0.000	

For 3D Models & 2D Sales Drawings

