

# METRIC TWO-PIECE CLAMPING COLLARS **M2C-SERIES**



- Easily installed where major disassembly would otherwise be required
- Design fully engages the shaft without marring
- Greater axial holding power than set screw or one-piece collars
- Effective on both hard and soft shafts

PART NUMBER		PRODUCT SPECIFICATIONS				
BLACK OXIDE STEEL	STAINLESS STEEL	BORE	OD (IN)	WIDTH	SCREW SIZE	APPROX WEIGHT (OZ)
M2C-03	M2C-03-S	3	1 1/16	9	M 3 x 8	0.40
M2C-04	M2C-04-S	4	1 1/16	9	M 3 x 8	0.40
M2C-05	M2C-05-S	5	1 1/16	9	M 3 x 8	0.40
M2C-06	M2C-06-S	6	3/4	9	M 3 x 8	0.46
M2C-07	M2C-07-S	7	3/4	9	M 3 x 8	0.43
M2C-08	M2C-08-S	8	1	9	M 3 x 10	0.90
M2C-09	M2C-09-S	9	1	9	M 3 x 10	0.81
M2C-10	M2C-10-S	10	1	9	M 3 x 10	0.80
M2C-12	M2C-12-S	12	1 1/8	11	M 4 x 12	1.31
M2C-13	M2C-13-S	13	1 1/4	11	M 4 x 12	1.50
M2C-14	M2C-14-S	14	1 1/4	11	M 4 x 12	1.50
M2C-15	M2C-15-S	15	1 3/8	13	M 5 x 16	2.30
M2C-16	M2C-16-S	16	1 3/8	13	M 5 x 16	2.25
M2C-17	M2C-17-S	17	1 1/2	13	M 5 x 16	2.60
M2C-18	M2C-18-S	18	1 1/2	13	M 5 x 16	2.40
M2C-19	M2C-19-S	19	1 5/8	15	M 6 x 16	3.61
M2C-20	M2C-20-S	20	1 5/8	15	M 6 x 16	3.41
M2C-21	M2C-21-S	21	1 3/4	15	M 6 x 16	3.90
M2C-22	M2C-22-S	22	1 3/4	15	M 6 x 16	3.71
M2C-23	M2C-23-S	23	1 7/8	15	M 6 x 16	4.45
M2C-24	M2C-24-S	24	1 7/8	15	M 6 x 16	4.20
M2C-25	M2C-25-S	25	1 7/8	15	M 6 x 16	4.80
M2C-26	M2C-26-S	26	2	15	M 6 x 16	4.00
M2C-28	M2C-28-S	28	2	15	M 6 x 16	4.40
M2C-30	M2C-30-S	30	2 1/8	15	M 6 x 16	5.90
M2C-32	M2C-32-S	32	2 1/8	15	M 6 x 16	5.50
M2C-34	M2C-34-S	34	2 1/4	15	M 6 x 16	6.11
M2C-35	M2C-35-S	35	2 1/4	15	M 6 x 16	5.90
M2C-36	M2C-36-S	36	2 1/4	15	M 6 x 16	5.70
M2C-38	M2C-38-S	38	2 3/8	15	M 6 x 16	6.31
M2C-40	M2C-40-S	40	2 3/8	15	M 6 x 16	5.70
M2C-42	M2C-42-S	42	2 7/8	19	M 8 x 25	13.50
M2C-45	M2C-45-S	45	2 7/8	19	M 8 x 25	12.50
M2C-48	M2C-48-S	48	3 1/8	19	M 8 x 25	14.10
M2C-50	M2C-50-S	50	3 1/8	19	M 8 x 25	13.50
M2C-54	M2C-54-S	54	3 1/4	19	M 8 x 25	14.30
M2C-55	M2C-55-S	55	3 1/4	19	M 8 x 25	14.00
M2C-60	M2C-60-S	60	3 1/2	19	M 8 x 25	15.50
M2C-65	M2C-65-S	65	3 3/4	19	M 8 x 25	16.70
M2C-70	M2C-70-S	70	4	19	M 8 x 25	17.70
M2C-75	M2C-75-S	75	4 1/4	19	M 8 x 25	18.80
M2C-80	M2C-80-S	80	4 1/4	19	M 8 x 25	19.70
BLACK OXIDE STEEL	STAINLESS STEEL	BORE	OD (MM)	WIDTH	SCREW SIZE	APPROX WEIGHT (OZ)
M2C-85	M2C-85-S	85	125	25	M 10 X 30	45.62
M2C-90	M2C-90-S	90	130	25	M 10 X 30	47.79
M2C-95	M2C-95-S	95	135	25	M 10 X 30	49.97
M2C-100	M2C-100-S	100	140	25	M 10 X 30	52.14
M2C-110	M2C-110-S	110	150	25	M 10 X 30	56.48
M2C-120	M2C-120-S	120	160	25	M 10 X 30	60.83
M2C-125	M2C-125-S	125	165	25	M 10 X 30	63.00
M2C-130	M2C-130-S	130	170	25	M 10 X 30	65.17
M2C-140	M2C-140-S	140	180	25	M 10 X 30	69.52
M2C-150	M2C-150-S	150	190	25	M 10 X 30	73.86

**DIMENSION**  
BORE, INCH

**TOLERANCE**  
+0.08MM / -0.00MM

For 3D  
Models &  
2D Sales  
Drawings

