

TWO-PIECE CLAMPING COLLARS RECESSED SCREW H2C-SERIES



- Recessed screw head provides an outside surface free of major projections for safety
- Easily installed where major disassembly would otherwise be required
- Design fully engages the shaft without marring
- Effective on both hard and soft shafts

PART NUMBER		PRODUCT SPECIFICATIONS				
BLACK OXIDE STEEL	STAINLESS STEEL	BORE	OD	WIDTH	SCREW SIZE	APPROX WEIGHT (OZ)
H2C-012	H2C-012-S	1/8	13/16	1/4	4-40 x 3/8	0.48
H2C-018	H2C-018-S	3/16	13/16	1/4	4-40 x 3/8	0.44
H2C-025	H2C-025-S	1/4	13/16	1/4	4-40 x 3/8	0.42
H2C-031	H2C-031-S	5/16	13/16	1/4	4-40 x 3/8	0.40
H2C-037	H2C-037-S	3/8	1 1/16	5/16	6-32 x 3/8	0.89
H2C-043	H2C-043-S	7/16	1 1/16	5/16	6-32 x 3/8	0.83
H2C-050	H2C-050-S	1/2	1 1/4	3/8	8-32 x 1/2	1.45
H2C-056	H2C-056-S	9/16	1 1/4	3/8	8-32 x 1/2	1.41
H2C-062	H2C-062-S	5/8	1 1/2	13/32	10-32 x 1/2	2.20
H2C-068	H2C-068-S	11/16	1 1/2	13/32	10-32 x 1/2	2.10
H2C-075	H2C-075-S	3/4	1 3/4	1/2	1/4-28 x 5/8	3.60
H2C-081	H2C-081-S	13/16	1 3/4	1/2	1/4-28 x 5/8	3.50
H2C-087	H2C-087-S	7/8	1 7/8	1/2	1/4-28 x 5/8	4.10
H2C-093	H2C-093-S	15/16	1 7/8	1/2	1/4-28 x 5/8	3.90
H2C-100	H2C-100-S	1	2	1/2	1/4-28 x 5/8	4.50
H2C-106	H2C-106-S	1 1/16	2	1/2	1/4-28 x 5/8	4.30
H2C-112	H2C-112-S	1 1/8	2 1/8	1/2	1/4-28 x 3/4	5.00
H2C-118	H2C-118-S	1 3/16	2 1/8	1/2	1/4-28 x 3/4	4.70
H2C-125	H2C-125-S	1 1/4	2 1/4	1/2	1/4-28 x 3/4	5.30
H2C-131	H2C-131-S	1 5/16	2 1/4	1/2	1/4-28 x 3/4	5.00
H2C-137	H2C-137-S	1 3/8	2 3/8	1/2	1/4-28 x 3/4	5.80
H2C-143	H2C-143-S	1 7/16	2 3/8	1/2	1/4-28 x 3/4	5.50
H2C-150	H2C-150-S	1 1/2	2 1/2	1/2	1/4-28 x 3/4	6.20
H2C-156	H2C-156-S	1 9/16	2 1/2	1/2	1/4-28 x 3/4	5.80
H2C-162	H2C-162-S	1 5/8	3	5/8	5/16-24 x 1	12.50
H2C-168	H2C-168-S	1 11/16	3	5/8	5/16-24 x 1	12.10
H2C-175	H2C-175-S	1 3/4	3	5/8	5/16-24 x 1	11.50
H2C-187	H2C-187-S	1 7/8	3 1/4	5/8	5/16-24 x 1	13.80
H2C-193	H2C-193-S	1 15/16	3 1/4	5/8	5/16-24 x 1	13.40
H2C-200	H2C-200-S	2	3 1/4	5/8	5/16-24 x 1	12.70
H2C-212	H2C-212-S	2 1/8	3 1/2	5/8	5/16-24 x 1	15.00
H2C-218	H2C-218-S	2 3/16	3 1/2	5/8	5/16-24 x 1	14.60
H2C-225	H2C-225-S	2 1/4	3 1/2	5/8	5/16-24 x 1	14.00
H2C-237	H2C-237-S	2 3/8	3 1/2	5/8	5/16-24 x 1	13.40
H2C-243	H2C-243-S	2 7/16	4	3/4	3/8-24 x 1	12.90
H2C-250	H2C-250-S	2 1/2	4	3/4	3/8-24 x 1	22.80
H2C-262	H2C-262-S	2 5/8	4 1/4	3/4	3/8-24 x 1	26.60
H2C-268	H2C-268-S	2 11/16	4 1/4	3/4	3/8-24 x 1	26.00
H2C-275	H2C-275-S	2 3/4	4 1/4	3/4	3/8-24 x 1	25.10
H2C-287	H2C-287-S	2 7/8	4 1/2	3/4	3/8-24 x 1	29.00
H2C-293	H2C-293-S	2 15/16	4 1/2	3/4	3/8-24 x 1	28.00
H2C-300	H2C-300-S	3	4 1/2	3/4	3/8-24 x 1	26.60
H2C-318	H2C-318-S	3 3/16	4 1/2	7/8	3/8-24 x 1	28.30
H2C-325	H2C-325-S	3 1/4	4 1/2	7/8	3/8-24 x 1	27.30
H2C-337	H2C-337-S	3 3/8	4 3/4	7/8	3/8-24 x 1	29.00
H2C-343	H2C-343-S	3 7/16	4 3/4	7/8	3/8-24 x 1	31.00
H2C-350	H2C-350-S	3 1/2	4 3/4	7/8	3/8-24 x 1	29.10
H2C-375	H2C-375-S	3 3/4	5	7/8	3/8-24 x 1	32.00
H2C-393	H2C-393-S	3 15/16	5 1/4	7/8	3/8-24 x 1	35.00
H2C-400	H2C-400-S	4	5 1/4	7/8	3/8-24 x 1	33.00
H2C-425	H2C-425-S	4 1/4	5 1/2	7/8	3/8-24 x 1	35.00
H2C-443	H2C-443-S	4 7/16	5 3/4	7/8	3/8-24 x 1	38.50
H2C-450	H2C-450-S	4 1/2	5 3/4	7/8	3/8-24 x 1	36.00
H2C-493	H2C-493-S	4 15/16	6 1/4	7/8	3/8-24 x 1	42.50
H2C-500	H2C-500-S	5	6 1/4	7/8	3/8-24 x 1	40.10
H2C-525	H2C-525-S	5 1/4	6 3/4	7/8	3/8-24 x 1	42.00
H2C-550	H2C-550-S	5 1/2	6 3/4	7/8	3/8-24 x 1	43.30
H2C-593	H2C-593-S	5 15/16	7 1/4	7/8	3/8-24 x 1	50.30
H2C-600	H2C-600-S	6	7 1/4	7/8	3/8-24 x 1	47.60

Bore sizes 3-3/16" through 6" do not have recessed screws

DIMENSION

BORE, INCH

TOLERANCE

+0.003 / -0.000



For 3D Models & 2D Sales Drawings