

Metric One-Piece Industry Standard Clamping Couplings - MISCC-Series

Black Oxide Steel	Stainless Steel	Bore Size	2nd Bore Size	OD	Length	Clamp Screw	Box Qty	Approx. Weight (oz.)
MISCC-06-06	MISCC-06-06-S	6	6	18	30	M 3 x 8	10	1.60
MISCC-08-08	MISCC-08-08-S	8	8	24	35	M 3 x 10	10	2.80
MISCC-09-09	MISCC-09-09-S	9	9	24	35	M 3 x 10	10	2.40
MISCC-10-10	MISCC-10-10-S	10	10	29	45	M 4 x 12	5	6.93
MISCC-12-12	MISCC-12-12-S	12	12	29	45	M 4 x 12	5	6.50
MISCC-14-14	MISCC-14-14-S	14	14	34	50	M 5 x 16	5	8.80
MISCC-15-15	MISCC-15-15-S	15	15	34	50	M 5 x 16	5	8.60
MISCC-16-16	MISCC-16-16-S	16	16	34	50	M 5 x 16	5	8.40
MISCC-20-20	MISCC-20-20-S	20	20	42	65	M 6 x 16	5	18.00
MISCC-25-25	MISCC-25-25-S	25	25	45	75	M 6 x 16	2	22.39
MISCC-30-30	MISCC-30-30-S	30	30	53	83	M 6 x 16	2	36.14
MISCC-35-35	MISCC-35-35-S	35	35	67	95	M 8 x 25	1	39.00
MISCC-40-40	MISCC-40-40-S	40	40	77	108	M 8 x 25	1	90.00
MISCC-50-50	MISCC-50-50-S	50	50	85	124	M 10 x 25	1	108.00



- High axial load and torque capacity
- Does not mar the shaft

Black Oxide Steel With Keyway	Stainless Steel With Keyway	Bore Size	2nd Bore Size	OD	Length	Clamp Screw	Box Qty	Approx. Weight (oz.)
MISCC-08-08-KW	MISCC-08-08-SKW	8	8	24	35	M 3 x 10	10	2.80
MISCC-09-09-KW	MISCC-09-09-SKW	9	9	24	35	M 3 x 10	10	2.40
MISCC-10-10-KW	MISCC-10-10-SKW	10	10	29	45	M 4 x 12	5	6.93
MISCC-12-12-KW	MISCC-12-12-SKW	12	12	29	45	M 4 x 12	5	6.50
MISCC-14-14-KW	MISCC-14-14-SKW	14	14	34	50	M 5 x 16	5	8.80
MISCC-15-15-KW	MISCC-15-15-SKW	15	15	34	50	M 5 x 16	5	8.60
MISCC-16-16-KW	MISCC-16-16-SKW	16	16	34	50	M 5 x 16	5	8.40
MISCC-20-20-KW	MISCC-20-20-SKW	20	20	42	65	M 6 x 16	5	18.00
MISCC-25-25-KW	MISCC-25-25-SKW	25	25	45	75	M 6 x 16	2	22.39
MISCC-30-30-KW	MISCC-30-30-SKW	30	30	53	83	M 6 x 16	2	36.14
MISCC-35-35-KW	MISCC-35-35-SKW	35	35	67	95	M 8 x 25	1	39.00
MISCC-40-40-KW	MISCC-40-40-SKW	40	40	77	108	M 8 x 25	1	90.00
MISCC-50-50-KW	MISCC-50-50-SKW	50	50	85	124	M 10 x 25	1	108.00



DIMENSION
Bore, mm

TOLERANCE
+.08/- .00mm